→ GUILLOTINE **IDEAL 4705**

POWERFUL MANUAL OFFICE GUILLOTINE WITH 475 MM CUTTING LENGTH

"SCS" - the Safety Cutting System made by IDEAL provides numerous safety features: hinged, transparent safety guard on the front table (locks automatically while cutting); transparent hand guard on the rear table; safety catch (locks blade lever in upper position); safe and convenient blade change from the front without removing machine covers; blade changing device with covered cutting edge; blade depth adjustment from the outside of the machine; cutting stick can be turned or replaced easily from the outside of the machine | cuts large formats of up to 475 mm in length | 70 mm cutting height | high-quality blade made from "Solingen steel" | solid steel blade carrier | solid spindle clamp with hand wheel | spindle guided backgauge with hand crank | measuring scale (mm/inches) on front table | solid all-metal construction | designed as table top machine, a stand is available as an option (at an extra cost)

Dimensions (H x W x D): 590/12701 x 1000 x 890 mm, Weight: 85 /931 kg, Colour: perl grey.



PRECISION BACKGAUGE





EASY CUTTING STICK CHANGE



SAFETY CATCH FOR BLADE



SAFETY GUARDS



Transparent safety guards made

from unbreakable Lexan® on

front and rear table: The hinged

front safety guard locks in the lower position while cutting.

SPINDLE CLAMP



The variable clamp pressure

is applied via the hand wheel to

both ends of the clamp for firm

pressure across the entire

cutting line.

MEASURING SCALE




The precise measuring scale

(mm/inches) for the backgauge

positioning can be read easily and

is located on the front table.

1 / IDEAL 4/03	
Cutting length	475 mm
Cutting height	70 mm
Narrow cut	30 mm
Table depth	455 mm
Measuring scale	mm/inches



→ GUILLOTINE IDEAL 4705 + ACCESSORIES

DESCRIPTION	ARTICLE NO.	EAN CODE
IDEAL 4705	47050000	4019364210051
Stand for IDEAL 4700/4705	47001100	4019364210204
Spare blade for IDEAL 4700/4705	9000021	4019364920202
Cutting sticks for IDEAL 4705 (6 pieces per packing unit)	9000222	4019364925221

