







Catena Series

Moderate Production Laminators

Designed to encapsulate and mount prints from color printers and copiers, the Catena Series provides a simple way to finish your full-color digital output. These models feature heated rollers that can also run pressure-sensitive films for moderate laminating production.

CATENA 35

This compact laminator is designed to provide safe and convenient lamination in offices and small print shops producing 8.5" x 11" prints.

CATENA 65 & 105

When productivity and profit count the most, the Catena 65 and 105 meet the requirements of your more demanding jobs. These larger units are able to handle a wider variety of applications including standard poster-sized prints.



Features and Benefits

EASY TO USE

- LCD display indicates temperature, speed and Ready/Wait condition.
- Silicone rubber rollers ensure timely clean-up.
- Interlocking feed tray and magnetic safety shield provide safe operation.

VERSATILE

- Designed for thermal and pressure-sensitive films.
- Roller gap adjustment handles mounting boards up to 3/16" thick.
- Rewind roller peels away pressure-sensitive release liner.



CATENA SERIES CONTROL PANEL

CONTROLS

• The user-friendly control panel allows the operator to make adjustments easily as needed for professionally laminated graphics.

SUPERIOR QUALITY

- Infrared heating coil distributes heat evenly and improves lamination quality.
- Microprocessor controls temperature and guarantees fast response time.
- Cooling fan ensures smooth, flat output.
- Will not interfere with electrical surroundings; no buzzing, humming or flickering lights.



Catena Series

Moderate Production Laminators

Specifications

	13" 25" 41"
Film Gauge:	1.5, 3, 5, and 10 mil
Core Diameter: Catena 35 Catena 65 & 105:	1" (Poly-in) 1" or 2.25"
Maximum Roll OD:	5" outside diameter
Speed:	1.5 fpm - 5 fpm
Dimensions: Catena 35: Catena 65: Catena 105:	25" W x 13" H x 18" D 39" W x 17" H x 18" D 51" W x 48" H x 21" D
	55 lbs. 84 lbs. 154 lbs.
Power & Safety: Catena 35 & 65: Catena 105:	120V, 60Hz, 12 amp; UL, CE, CSA Listed 220V, 50-60Hz, 15 amp; UL, CE,

CSA Listed

Films

Octiva® Thermal Octiva® Lo-Melt Arctic[®] Pressure Sensitive GBC_® Hi-Tac Polyester

Applications



> Placemats

USA



> Posters



> Certificates



> POP Displays

Visit GBC at www.gbcconnect.com





712 W. Winthrop Avenue Addison, IL 60101-4395 800-772-9281 www.gbcconnect.com