

The A3 'Office Standard'

The ideal laminator for multiple users which gives the user the freedom to laminate using hot applications from 2x75mic (150Total) to 2x250mic (500 Total) and additional cold temp setting for GBC cold seal pouches.

H425 is perfect for multi purpose applications in an med to high volume lamination office!

- **Simple clear** user guidelines for temperature settings
- Lamination width* from ID size to **A3 Max** (324 mm).
- Ideal for use with GBC **High speed** pouches
- Carrier-free performance
- Digital Variable Temperature control giving increased accuracy (+ 'Cold' setting)

4 Roller Technology for exceptionally high quality lamination results!

Features & Benefits

- 1 Variable digital temperature control:** For photo quality results from 2x75mic to 2x250mic. Great flexibility for user to be creative with lamination.
- 2 Simple clear & stylish user temperature guidelines.** Clear colour table to help user get best results
- 3 Fixed Speed:**
 - Time to laminate 1 A4 sheet with Standard Pouch: 45 sec
 - Time to laminate 1 A4 sheet with a High Speed Pouch: 31.5 sec
 - Use High Speed Pouches to increase productivity without compromising on quality
- 4 Fast warm up time of only 5 minutes.**
- 5 Exit Tray-** Keeps the laminated product straight on exit minimising curling and warping
- 6 Reverse Button** Anti-jam function to solve any miss-feeding problems



Technical Specifications

Photo quality	Yes
Heat-up Time (75 mic)	5 min.
Speed mm/min.	400
Temperature control	Digital control Variable
Cold Lamination	Yes
Speed control	Fixed
Rollers	4
Max. Document size	A3 320 mm
Max. pouch thickness	2x250 Micron (Total 500)

Ready Light	Yes
Release Function	Yes
Display	-

Pouch counter	-
Auto switch off	Yes
Time to laminate	
1 Standard A4 Pouch	45 sec.
A4 Laminates / hr*	80
Time to laminate	
1 High Speed Pouch	32 sec.
High Speed Pouches	Yes
Laminates / hr*	114
Warranty	2 years
Dimensions	615x185x240
Certification	GS / TÜV / CE
Weight	5.5 kg
Power Consumption	
Amps	3.5A

Product Codes:

EU 1702820

UK 1702830

